

SIMPLY-CLAY Termination Bar

Exterior Below-Grade Commercial Bentonite Waterproofing System

Description

SIMPLY-CLAY Termination Bar is a high strength vinyl/plastic strip designed for attaching and sealing SIMPLY-CLAY membranes and drainage layers at their termination points. Term bar is 1" wide has pre-drilled holes and edging for caulking and sealing.

Installation

Surface should be clean, dry and free of contaminants. Install SIMPLY-CLAY Termination bar at the top edge of material that it is to be supported. Fasten into substrate using pre-drilled holes with appropriate mechanical or power actuated fasteners. Apply a bead of silicone caulk to top of termination bar after application is complete. For specific installation guidelines, please contact our distributor, a Simply Waterproofing Representative, or visit our website at www.SimplyWaterproofing.com for details.

SIMPLY WATERPROOFING products support sustainable and energy-efficient building practices, including efforts toward achieving LEED® certification (LEED® for New Construction & Major Renovations, LEED® for Core and Shell, LEED® for Existing Buildings and LEED® for Homes).

For Technical Support contact Simply Waterproofing via email at: info@simplywaterproofing.com or visit www.simplywaterproofing.com.

Packaging

Cartons contain 50-6'6" strips per box.

Storage

Protect from moisture. Store in original shipping container on skid or pallet, cover with polyethylene or tarp.

Availability

Available internationally and nationally through Simply Waterproofing distributors. Contact us for details.

Limitations

Products as described herein are for industrial use only. The application procedures should be performed by workmen who are skilled in the application of material described herein in accordance with manufacturer specifications. Installation temperature is between -40°F to 150°F (-40°C to 65.5°C).

Limited Warranty

Simply Waterproofing Products warrants its products will be delivered free of defects in materials and workmanship. Simply Waterproofing will replace the material or refund the purchase price. Simply Waterproofing makes no other warranty, including an implied warranty of merchantability or fitness for a particular purpose. Simply Waterproofing shall not be liable for any other loss or damage. Contact Simply Waterproofing to discuss specific details for extended warranty periods.

HEALTH AND SAFETY INFORMATION IS GIVEN IN THE SAFETY DATA SHEET (SDS) AND THE PRODUCT DATA SHEET AVAILABLE FOR THIS PRODUCT. THESE SHOULD BE READ AND UNDERSTOOD BEFORE USING THIS PRODUCT.